

## Datenblatt

030PPFIR

Flächenbündiger Drucktaster, permanent, rot



## Merkmale

|                        |   |
|------------------------|---|
| <b>Baureihe</b>        | Unbeleuchtete Taster Ø 30                   |
| <b>Komponenten</b>     | Drucktaster mit Frontring                   |
| <b>Artikel-Nr.</b>     | 030PPFIR                                    |
| <b>Beschreibung</b>    | Flächenbündiger Drucktaster, permanent, rot |
| <b>Farbe</b>           | Rosso                                       |
| <b>Gewicht - gr</b>    | 35,0  |
| <b>Zolltarifnummer</b> | 85365080                                    |
| <b>GTIN</b>            | 8052878032098                               |

## Technische Daten

|  |  |
|--|--|
| <b>Approvals</b>                         | CE, UL, CSA                                      |
| <b>Compliance with standards</b>         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| <b>Compliance with standards</b>         | UNI CEI EN 45545-2, CEI EN 61373                 |
| <b>Operating temperatures</b>            | -25° ÷ +65°C                                     |
| <b>Environmental operating values</b>    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)     |
| <b>Protection degree</b>                 | IP65 (IEC-EN60529)                               |
| <b>Protection against impact</b>         | IK04 (IEC-EN62262)                               |
| <b>Mechanical durability</b>             | 500.000 Operations                               |
| <b>Shock resistance</b>                  | 30g duration=18ms (EN-IEC 60068-2-27)            |
| <b>Shock resistance</b>                  | 50g duration=11ms (EN-IEC 60068-2-27)            |
| <b>Vibration resistance</b>              | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| <b>Contact blocks configuration</b>      | Max no. 4 blocks (2+2)                           |
| <b>Button or knob material</b>           | PA Polyamide                                     |
| <b>External bezel material</b>           | Anodized aluminum                                |
| <b>Locking ring material</b>             | Zamak zinc alloy                                 |
| <b>Fixing diameter</b>                   | 30.5mm - Thickness 1÷6mm                         |
| <b>Tightening torque</b>                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| <b>Actuation type</b>                    | Push-Push (maintained position)                  |
| <b>Protection against electric shock</b> | Class I (IEC-EN61140)                            |
| <b>Warranty period</b>                   | 18 months  |

# Technische Zeichnungen

