


Scheda Dati

030RFFPMRFAFC

Noodstopkop Ø 60, tijdelijk, rood, metalen bescherming, N.O.+N.C.



Caratteristiche

Bereik	Niet-verlichte paddestoelknoppen Ø 30
Componente	Noodstopknoppen Ø 60, metalen bescherming
Rubriek	030RFFPMRFAFC
Omschrijving	Noodstopkop Ø 60, tijdelijk, rood, metalen bescherming, N.O.+N.C.
Kleur	Rosso
Peso	162,0
Tariffa doganale	85365080
GTIN	8052878033255

Dati tecnici

Approvals	CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	3.000.000 Operations
Button/mushroom material (illuminated type)	PC Polycarbonate
External bezel material	Chromed zinc alloy
Housing material	PA Polyamide + chrome
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	Spring return
Protection against electric shock	Class II (IEC-EN61140)
Contact block	Included
Contact block characteristics	See technical features of 030FAP - 030FCP - 030F1P
Warranty period	18 months

Disegni tecnici

