



## Scheda Dati

030RFFVF1

Bouton-poussoir coup de poing Ø 60, momentané, vert, N.O.+N.C.



## Caratteristiche

|                              |  |
|------------------------------|--|
| Portée                       | Boutons-poussoirs coup de poing non-lumineux Ø 30              |
| Componente                   | Coup de poing Ø 60   |
| Code                         | 030RFFVF1  |
| Désignation des marchandises | Bouton-poussoir coup de poing Ø 60, momentané, vert, N.O.+N.C. |
| Couleur                      | Verde  |
| Peso                         | 130,0  |
| Tariffa doganale             | 85365080   |
| GTIN                         | 8052878033361  |

## Dati tecnici

|   |  |
|---|--|
| Approvals                                   | CE, UL, CSA  |
| Compliance with standards                   | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| Operating temperatures                      | -25° ÷ +65°C                                       |
| Protection degree                           | IP65 (IEC-EN60529)                                 |
| Mechanical durability                       | 3.000.000 Operations                               |
| Button/mushroom material (illuminated type) | PC Polycarbonate                                   |
| Housing material                            | PA Polyamide                                       |
| External bezel material                     | Chromed zinc alloy                                 |
| Fixing diameter                             | 30.5mm - Thickness 1÷6mm                           |
| Tightening torque                           | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                        |
| Actuation type                              | Spring return                                      |
| Protection against electric shock           | Class II (IEC-EN61140)                             |
| Contact block                               | Included   |
| Contact block characteristics               | See technical features of 030FAP - 030FCP - 030F1P |
| Warranty period                             | 18 months  |

## Disegni tecnici

