# Fiche technique

030RFLRFAFC24

Bouton-poussoir coup de poing Ø 35, lumineux, momentané, rouge, led BA9S 24V, N.O.+N.C.





## Caractéristiques

| | |
|---|---|
| **Portée** | Boutons-poussoirs coup de poing lumineux Ø 30 |
| **Composant** | Coup de poing Ø 35 |
| **Code** | 030RFLRFAFC24 |
| **Désignation des marchandises** | Bouton-poussoir coup de poing Ø 35, lumineux, momentané, rouge, led BA9S 24V, N.O.+N.C. |
| **Couleur** | Rosso |
| **Poids** | 101,0 |
| **Tarif douanier** | 85365080 |
| **GTIN** | 8052878033446 |

## Données techniques

| | |
|---|---|
| **Approvals** | CE, UL, CSA |
| **Compliance with standards** | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| **Operating temperatures** | -25° ÷ +65°C |
| **Protection degree** | IP65 (IEC-EN60529) |
| **Mechanical durability** | 3.000.000 Operations |
| **Material** | PA Polyamide |
| **Button/mushroom material (illuminated type)** | PC Polycarbonate |
| **External bezel material** | Chromed zinc alloy |
| **Fixing diameter** | 30.5mm - Thickness 1÷6mm |
| **Tightening torque** | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| **Bulb type** | Ba9S LED 24V AC-DC (included) |
| **Contact block** | Included |
| **Contact block characteristics** | See technical features of 030FAP - 030FCP - 030F1P |
| **Warranty period** | 18 months |

## Dessins techniques







