


# Datasheet

030RICGAF1

Push-button with guard, orange, N.O.+N.C., rubber cap



## Features

|                |   |
|----------------|---|
| Range          | Non-illuminated push-buttons Ø 30                     |
| components     | With guard and cap                                    |
| Code           | 030RICGAF1  |
| Description    | Push-button with guard, orange, N.O.+N.C., rubber cap |
| Colour         | Arancio   |
| Weight - gr    | 86.0  |
| Customs Tariff | 85365080  |
| GTIN           | 8052878069353   |

## Datasheet

|                                   |  |
|-----------------------------------|--|
| Approvals                         | CE   |
| Compliance with standards         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures            | -25° ÷ +65°C                                     |
| Protection degree                 | IP66 - IP69 (IEC-EN60529)                        |
| Mechanical durability             | 3.000.000 Operations                             |
| Housing material                  | PA Polyamide                                     |
| Fixing diameter                   | 30.5mm - Thickness 1÷6mm                         |
| Actuation type                    | Spring return                                    |
| Protection against electric shock | Class II (IEC-EN61140)                           |
| Contact block characteristics     | See technical features of 030F1 or 030FA+030FCR  |
| Contact block                     | Included   |
| Cap material                      | Anodized aluminium ring and silicon rubber cap   |
| Tightening torque                 | 1 ÷ 2Nm (8.85 ÷ 17.70 Lb-in)                     |
| Cap Colour                        | Transparent                                      |
| Warranty period                   | 18 months  |

# Technical drawings

