


## Datasheet

030RICGBLF1

Push-button with guard, blue, N.O.+N.C., rubber cap



## Features

<b>Range</b>	Non-illuminated push-buttons Ø 30
<b>components</b>	With guard and cap
<b>Code</b>	030RICGBLF1
<b>Description</b>	Push-button with guard, blue, N.O.+N.C., rubber cap
<b>Colour</b>	Blu
<b>Weight - gr</b>	86.0
<b>Customs Tariff</b>	85365080
<b>GTIN</b>	8052878069346

## Datasheet

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Operating temperatures</b>	-25° ÷ +65°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Mechanical durability</b>	3.000.000 Operations
<b>Housing material</b>	PA Polyamide
<b>Fixing diameter</b>	30.5mm - Thickness 1÷6mm
<b>Actuation type</b>	Spring return
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Contact block characteristics</b>	See technical features of 030F1 or 030FA+030FCR
<b>Contact block</b>	Included
<b>Cap material</b>	Anodized aluminium ring and silicon rubber cap
<b>Tightening torque</b>	1 ÷ 2Nm (8.85 ÷ 17.70 Lb-in)
<b>Cap Colour</b>	Transparent
<b>Warranty period</b>	18 months

# Technical drawings

