

Fiche technique

030RICGBLF1

Bouton-poussoir affleurant, bleu, N.O.+N.C., capuchon caoutchouc



Caractéristiques

Portée	Boutons-poussoirs non-lumineux Ø 30
Composant	Affleurants et capuchon
Code	030RICGBLF1
Désignation des marchandises	Bouton-poussoir affleurant, bleu, N.O.+N.C., capuchon caoutchouc
Couleur	Blu
Poids	86,0
Tarif douanier	85365080
GTIN	8052878069346

Données techniques

Approvals	CE
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Mechanical durability	3.000.000 Operations
Housing material	PA Polyamide
Fixing diameter	30.5mm - Thickness 1÷6mm
Actuation type	Spring return
Protection against electric shock	Class II (IEC-EN61140)
Contact block characteristics	See technical features of 030F1 or 030FA+030FCR
Contact block	Included
Cap material	Anodized aluminium ring and silicon rubber cap
Tightening torque	1 ÷ 2Nm (8.85 ÷ 17.70 Lb-in)
Cap Colour	Transparent
Warranty period	18 months

Dessins techniques

