

Scheda Dati

030RICGRF1

Drukknop met bescherming, rood, N.O.+N.C., rubberen kap



Caratteristiche

Bereik	Niet-verlichte drukknoppen Ø 30
Componente	Drukknoppen met bescherming en kap
Rubriek	030RICGRF1
Omschrijving	Drukknop met bescherming, rood, N.O.+N.C., rubberen kap
Kleur	Rosso
Peso	86,0
Tariffa doganale	85365080
GTIN	8052878069315

Dati tecnici

Approvals	CE
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Mechanical durability	3.000.000 Operations
Housing material	PA Polyamide
Fixing diameter	30.5mm - Thickness 1÷6mm
Actuation type	Spring return
Protection against electric shock	Class II (IEC-EN61140)
Contact block characteristics	See technical features of 030F1 or 030FA+030FCR
Contact block	Included
Cap material	Anodized aluminium ring and silicon rubber cap
Tightening torque	1 ÷ 2Nm (8.85 ÷ 17.70 Lb-in)
Cap Colour	Transparent
Warranty period	18 months

Disegni tecnici

