

Fiche technique

030RICGVF1

Bouton-poussoir affleurant, vert, N.O.+N.C., capuchon caoutchouc



Caractéristiques

| | |
|-------------------------------------|--|
| Portée | Boutons-poussoirs non-lumineux Ø 30 |
| Composant | Affleurants et capuchon |
| Code | 030RICGVF1 |
| Désignation des marchandises | Bouton-poussoir affleurant, vert, N.O.+N.C., capuchon caoutchouc |
| Couleur | Verde |
| Poids | 86,0 |
| Tarif douanier | 85365080 |
| GTIN | 8052878069322 |

Données techniques

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +65°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Mechanical durability | 3.000.000 Operations |
| Housing material | PA Polyamide |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Actuation type | Spring return |
| Protection against electric shock | Class II (IEC-EN61140) |
| Contact block characteristics | See technical features of 030F1 or 030FA+030FCR |
| Contact block | Included |
| Cap material | Anodized aluminium ring and silicon rubber cap |
| Tightening torque | 1 ÷ 2Nm (8.85 ÷ 17.70 Lb-in) |
| Cap Colour | Transparent |
| Warranty period | 18 months |

