

Datasheet

030RPLRFAFC24

Projecting push-button, illuminated, momentary, red, led BA9S 24V, N.O.+N.C.



Features

Range	Illuminated push-buttons Ø 30
components	Projecting
Code	030RPLRFAFC24
Description	Projecting push-button, illuminated, momentary, red, led BA9S 24V, N.O.+N.C.
Colour	Rosso
Weight - gr	101.0
Customs Tariff	85365080
GTIN	8052878034320

Datasheet

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	3.000.000 Operations
Material	PA Polyamide
Button/mushroom material (illuminated type)	PC Polycarbonate
External bezel material	Chromed zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Bulb type	Ba9S LED 24V AC-DC (included)
Contact block	Included
Contact block characteristics	See technical features of 030FAP - 030FCP - 030F1P
Warranty period	18 months

Technical drawings

