

Fiche technique

030RPLSBFAFC24

Bouton-poussoir affleurant, lumineux, collerette complète, momentané, blanc, led BA9S 24V, N.O.+N.C.



Caractéristiques

Portée	Boutons-poussoirs lumineux Ø 30
Composant	Affleurants, collerette complète
Code	030RPLSBFAFC24
Désignation des marchandises	Bouton-poussoir affleurant, lumineux, collerette complète, momentané, blanc, led BA9S 24V, N.O.+N.C.
Couleur	Bianco
Poids	107,0
Tarif douanier	85365080
GTIN	8052878034337

Données techniques

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	3.000.000 Operations
Material	PA Polyamide
Button/mushroom material (illuminated type)	PC Polycarbonate
External bezel material	Chromed zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Bulb type	Ba9S LED 24V AC-DC (included)
Contact block	Included
Contact block characteristics	See technical features of 030FAP - 030FCP - 030F1P
Warranty period	18 months

Dessins techniques

