

## Fiche technique

030RPLSBFAFC24

Bouton-poussoir affleurant, lumineux, collerette complète, momentané, blanc, led BA9S 24V, N.O.+N.C.



## Caractéristiques

|                                     |  |
|-------------------------------------|--|
| <b>Portée</b>                       | Boutons-poussoirs lumineux Ø 30  |
| <b>Composant</b>                    | Affleurants, collerette complète   |
| <b>Code</b>                         | 030RPLSBFAFC24   |
| <b>Désignation des marchandises</b> | Bouton-poussoir affleurant, lumineux, collerette complète, momentané, blanc, led BA9S 24V, N.O.+N.C. |
| <b>Couleur</b>                      | Bianco   |
| <b>Poids</b>                        | 107,0  |
| <b>Tarif douanier</b>               | 85365080   |
| <b>GTIN</b>                         | 8052878034337  |

## Données techniques

|  |  |
|--|--|
| <b>Approvals</b>                                   | CE, UL, CSA  |
| <b>Compliance with standards</b>                   | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| <b>Operating temperatures</b>                      | -25° ÷ +65°C                                       |
| <b>Protection degree</b>                           | IP65 (IEC-EN60529)                                 |
| <b>Mechanical durability</b>                       | 3.000.000 Operations                               |
| <b>Material</b>                                    | PA Polyamide                                       |
| <b>Button/mushroom material (illuminated type)</b> | PC Polycarbonate                                   |
| <b>External bezel material</b>                     | Chromed zinc alloy                                 |
| <b>Fixing diameter</b>                             | 30.5mm - Thickness 1÷6mm                           |
| <b>Tightening torque</b>                           | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                        |
| <b>Bulb type</b>                                   | Ba9S LED 24V AC-DC (included)                      |
| <b>Contact block</b>                               | Included   |
| <b>Contact block characteristics</b>               | See technical features of 030FAP - 030FCP - 030F1P |
| <b>Warranty period</b>                             | 18 months  |

## Dessins techniques

