

Scheda Dati

030RPLSBFAFC24

Lichtdrukknop met complete bescherming, momentaan, wit,



Caratteristiche

Bereik	Lichtdrukknoppen Ø 30
Componente	Drukknoppen met complete bescherming
Rubriek	030RPLSBFAFC24
Omschrijving	Lichtdrukknop met complete bescherming, momentaan, wit,
Kleur	Bianco
Peso	100,0
Tariffa doganale	85365080
GTIN	8052878034337

Dati tecnici

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	3.000.000 Operations
Material	PA Polyamide
Button/mushroom material (illuminated type)	PC Polycarbonate
External bezel material	Chromed zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Bulb type	Ba9S LED 24V AC-DC (included)
Contact block	Included
Contact block characteristics	See technical features of 030FAP - 030FCP - 030F1P
Warranty period	18 months

Disegni tecnici

