

Datasheet

030RPLSRFAFC24

Push-button, full guard, illuminated, momentary, red, led BA9S 24V, N.O.+N.C.



Features

| | |
|-----------------------|---|
| Range | Illuminated push-buttons Ø 30 |
| components | With full guard |
| Code | 030RPLSRFAFC24 |
| Description | Push-button, full guard, illuminated, momentary, red, led BA9S 24V, N.O.+N.C. |
| Colour | Rosso |
| Weight - gr | 107.0 |
| Customs Tariff | 85365080 |
| GTIN | 8052878034368 |

Datasheet

| | |
|--------------------------------------|--|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +65°C |
| Protection degree | IP65 (IEC-EN60529) |
| Mechanical durability | 1.000.000 Operations |
| Housing material | PA Polyamide |
| Knob or lever material | PC Polycarbonate |
| External bezel material | Chromed zinc alloy |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Bulb type | Ba9S LED 24V AC-DC (included) |
| Contact block | Included |
| Contact block characteristics | See technical features of 030FAP - 030FCP - 030F1P |

Technical drawings

