



## Scheda Dati

030RRRFA

Ulostyöntyvä painike, punainen, N.O.



## Caratteristiche

Range	Normaalit painikkeet Ø 30
Componente	Ulostyöntyvät painikkeet
Code	030RRRFA
Kuvaus	Ulostyöntyvä painike, punainen, N.O.
Väriä	Rosso
Peso	68,0
Tariffa doganale	85365080
GT	8052878034566

## Dati tecnici

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	3.000.000 Operations
Button/mushroom material (illuminated type)	PC Polycarbonate
Housing material	PA Polyamide
External bezel material	Chromed zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	Spring return
Protection against electric shock	Class II (IEC-EN61140)
Contact block	Included
Contact block characteristics	See technical features of 030FAP - 030FCP - 030F1P
Warranty period	18 months

# Disegni tecnici

