


Scheda Dati

030RSLNV2F1

Seletor de alavanca, preto, 5 posições, Cam V, 2 N.O.+ N.C.



Caratteristiche



Gama	Seletores de alavanca Ø 30
Componente	Seletores de alavanca de 5 posições
Código	030RSLNV2F1
Descrição	Seletor de alavanca, preto, 5 posições, Cam V, 2 N.O.+ N.C.
Cor	Nero
Peso	117,0
Tariffa doganale	85365080
GTIN	8052878034993

Dati tecnici

Approvals	CE, UL, CSA, EAC
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	1.000.000 Operations
Housing material	PA Polyamide
Knob or lever material	PC Polycarbonate
External bezel material	Chromed zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Contact block	Included
Contact block characteristics	See technical features of 030FAP - 030FCP - 030F1P
Warranty period	18 months

Disegni tecnici

CAM V



33 — 34

11 — 12



43 — 44

21 — 22

