


Scheda Dati

030RSMNT2F1

Seletor de manípulo, preto, 3 posições, Cam T, 2 N.O.+ N.C.



Caratteristiche



| | |
|-------------------------|---|
| Gama | Seletores de manípulo Ø 30 |
| Componente | Seletores de manípulo de 3 posições |
| Código | 030RSMNT2F1 |
| Descrição | Seletor de manípulo, preto, 3 posições, Cam T, 2 N.O.+ N.C. |
| Cor | Nero |
| Peso | 124,0 |
| Tariffa doganale | 85365080 |
| GTIN | 8052878035228 |

Dati tecnici

| | |
|--|--|
| Approvals | CE, UL, CSA, EAC |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +65°C |
| Protection degree | IP65 (IEC-EN60529) |
| Mechanical durability | 1.000.000 Operations |
| Housing material | PA Polyamide |
| Knob or lever material | PC Polycarbonate |
| External bezel material | Chromed zinc alloy |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Contact block | Included |
| Contact block characteristics | See technical features of 030FAP - 030FCP - 030F1P |
| Warranty period | 18 months |

Disegni tecnici

CAM T



33 — 34

11 — 12

43 — 44

21 — 22

