


## Fiche technique

030RSMNV2F1

Bouton tournant à manette, noir, 5 positions, Cam V, 2 N.O.+2 N.C.



## Caractéristiques


|                                     |  |
|-------------------------------------|--|
| <b>Portée</b>                       | Boutons tournants à manette non-lumineux Ø 30                      |
| <b>Composant</b>                    | 5 positions  |
| <b>Code</b>                         | 030RSMNV2F1  |
| <b>Désignation des marchandises</b> | Bouton tournant à manette, noir, 5 positions, Cam V, 2 N.O.+2 N.C. |
| <b>Couleur</b>                      | Nero   |
| <b>Poids</b>                        | 124,0  |
| <b>Tarif douanier</b>               | 85365080   |
| <b>GTIN</b>                         | 8052878035266  |

## Données techniques

|  |  |
|--|--|
| <b>Approvals</b>                         | CE, UL, CSA, EAC                                   |
| <b>Compliance with standards</b>         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| <b>Operating temperatures</b>            | -25° ÷ +65°C                                       |
| <b>Protection degree</b>                 | IP65 (IEC-EN60529)                                 |
| <b>Mechanical durability</b>             | 1.000.000 Operations                               |
| <b>Housing material</b>                  | PA Polyamide                                       |
| <b>Knob or lever material</b>            | PC Polycarbonate                                   |
| <b>External bezel material</b>           | Chromed zinc alloy                                 |
| <b>Fixing diameter</b>                   | 30.5mm - Thickness 1÷6mm                           |
| <b>Tightening torque</b>                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                        |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                             |
| <b>Contact block</b>                     | Included   |
| <b>Contact block characteristics</b>     | See technical features of 030FAP - 030FCP - 030F1P |
| <b>Warranty period</b>                   | 18 months  |

# Dessins techniques

## CAM V



33 — 34

11 — 12



43 — 44

21 — 22

