

## Datenblatt

030SCSF1

Schlüssel-Wahlschalter , 3 Positionen, K95-Schlüssel, Cam S, Schlüsselabzug I-II, N.O.+N.C.,



## Merkmale

<b>Baureihe</b>	Schlüssel-Wahlschalter Ø 30
<b>Komponenten</b>	Schlüssel-Wahlschalter, 3 Positionen
<b>Artikel-Nr.</b>	030SCSF1
<b>Beschreibung</b>	Schlüssel-Wahlschalter , 3 Positionen, K95-Schlüssel, Cam S, Schlüsselabzug I-II, N.O.+N.C.,
<b>Gewicht - gr</b>	148,0
<b>Zolltarifnummer</b>	85365080
<b>GTIN</b>	8052878036027

## Technische Daten

<b>Approvals</b>	CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Operating temperatures</b>	-25° ÷ +65°C
<b>Protection degree</b>	IP65 (IEC-EN60529)
<b>Mechanical durability</b>	1.000.000 Operations
<b>Housing material</b>	PA Polyamide
<b>Knob or lever material</b>	PC Polycarbonate
<b>External bezel material</b>	Chromed zinc alloy
<b>Housing material</b>	PA Polyamide + chrome
<b>Fixing diameter</b>	30.5mm - Thickness 1÷6mm
<b>Tightening torque</b>	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Contact block</b>	Included
<b>Contact block characteristics</b>	See technical features of 030FAP - 030FCP - 030F1P
<b>Warranty period</b>	18 months

# Technische Zeichnungen



## CAM S

