


Scheda Dati

030SCT2F17

Bouton tournant à clé, 3 positions, clé K95, Cam T, retrait clé 0-II, 2 N.O.+2 N.C.




Caratteristiche

Portée	Boutons tournants à clé Ø 30
Componente	3 positions
Code	030SCT2F17
Désignation des marchandises	Bouton tournant à clé, 3 positions, clé K95, Cam T, retrait clé 0-II, 2 N.O.+2 N.C.
Peso	180,0
Tariffa doganale	85365080
GTIN	8052878036096



Dati tecnici

Approvals	CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	1.000.000 Operations
Housing material	PA Polyamide
Knob or lever material	PC Polycarbonate
External bezel material	Chromed zinc alloy
Housing material	PA Polyamide + chrome
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Contact block	Included
Contact block characteristics	See technical features of 030FAP - 030FCP - 030F1P
Warranty period	18 months

Disegni tecnici



CAM T



33 — 34

11 — 12

43 — 44

21 — 22

