

Fiche technique

030SFCA

Bouton tournant à clé, montage affleurant, 2 positions, clé K95, Cam A, retrait clé I-II



Caractéristiques

Portée	Boutons tournants à clé Ø 30
Composant	2 positions
Code	030SFCA
Désignation des marchandises	Bouton tournant à clé, montage affleurant, 2 positions, clé K95, Cam A, retrait clé I-II
Poids	82,0
Tarif douanier	85365080
GTIN	8052878036218

Données techniques

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-25° ÷ +65°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK04 (IEC-EN62262)
Mechanical durability	1.000.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 6 blocks (3+3)
External bezel material	Anodized aluminum
Knob or lever material	PA Polyamide
Locking ring material	Zamak zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Protection against electric shock	Class I (IEC-EN61140)
Warranty period	18 months



Dessins techniques

CAM A



020E10
020G

CAM A



020E01
020E10
020G

