

## Scheda Dati

030SFKQOC

Vierkante sleutelschakelaar, inbouwmodel, 3 posities, retour naar midden, Cam O



## Caratteristiche

|                         |   |
|-------------------------|---|
| <b>Bereik</b>           | Vierkante sleutelschakelaars Ø 30   |
| <b>Componente</b>       | Vierkante sleutelschakelaars 3 posities   |
| <b>Rubriek</b>          | 030SFKQOC   |
| <b>Omschrijving</b>     | Vierkante sleutelschakelaar, inbouwmodel, 3 posities, retour naar midden, Cam O |
| <b>Peso</b>             | 110,0   |
| <b>Tariffa doganale</b> | 85365080  |
| <b>GTIN</b>             | 8052878036485   |

## Dati tecnici

|  |  |
|--|--|
| <b>Approvals</b>                         | CE   |
| <b>Compliance with standards</b>         | UNI CEI EN 45545-2, CEI EN 61373             |
| <b>Compliance with standards</b>         | IEC-ENC60947-1, IEC-EN60947-5-1              |
| <b>Operating temperatures</b>            | -25° ÷ +70°C                                 |
| <b>Environmental operating values</b>    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| <b>Protection degree</b>                 | IP66 - IP69 (IEC-EN60529)                    |
| <b>Protection against impact</b>         | IK10 (IEC-EN62262)                           |
| <b>Mechanical durability</b>             | 1.000.000 Operations                         |
| <b>Shock resistance</b>                  | 30g duration=18ms (EN-IEC 60068-2-27)        |
| <b>Shock resistance</b>                  | 50g duration=11ms (EN-IEC 60068-2-27)        |
| <b>Vibration resistance</b>              | 5g f= 2...500Hz (EN-IEC 60068-2-6)           |
| <b>Contact blocks configuration</b>      | Max no. 6 blocks (3+3)                       |
| <b>Fixing diameter</b>                   | 30.5mm - Thickness 1÷6mm                     |
| <b>Protection against electric shock</b> | Class I (IEC-EN61140)                        |
| <b>Housing material</b>                  | Stainless steel AISI 304                     |
| <b>Square key insert material</b>        | Stainless steel AISI 304                     |
| <b>Locking ring material</b>             | Stainless steel AISI 304                     |
| <b>Locking ring tightening torque</b>    | 3÷5Nm (26.6÷44.3 Lb-in)                      |
| <b>Actuation torque</b>                  | 0.4Nm (3.5 Lb-in)                            |
| <b>Warranty period</b>                   | 18 months                                    |

# Disegni tecnici

