

Datablad

030SFLAN

Hendelschakelaar, zwart, inbouwmodel, 2 posities, I-II ,Cam A



Kenmerken


| | |
|---------------------|---|
| Bereik | Hendelschakelaars Ø 30 |
| Component | 2-positie hendelschakelaars |
| Rubriek | 030SFLAN |
| Omschrijving | Hendelschakelaar, zwart, inbouwmodel, 2 posities, I-II ,Cam A |
| Kleur | Nero |
| Gewicht | 39,0 |
| Douanetarief | 85365080 |
| GTIN | 8052878036515 |

Technische gegevens

| | |
|--|--|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373 |
| Operating temperatures | -25° ÷ +65°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP65 (IEC-EN60529) |
| Protection against impact | IK04 (IEC-EN62262) |
| Mechanical durability | 1.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 6 blocks (3+3) |
| External bezel material | Anodized aluminum |
| Knob or lever material | PA Polyamide |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Protection against electric shock | Class I (IEC-EN61140) |
| Warranty period | 18 months |

Technische tekeningen

CAM A



CAM A

