# Datasheet

030SFMAN
Knob selector switch, black, flush-mount, 2-position, Cam A





## Features

| | |
|---|---|
| **Range** | Non-illuminated knob selector switches Ø 30 |
| **components** | 2-position |
| **Code** | 030SFMAN |
| **Description** | Knob selector switch, black, flush-mount, 2-position, Cam A |
| **Colour** | Nero |
| **Weight - gr** | 45.7 |
| **Customs Tariff** | 85365080 |
| **GTIN** | 8052878036744 |


## Datasheet

| | |
|---|---|
| **Approvals** | CE, UL, CSA |
| **Compliance with standards** | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| **Compliance with standards** | UNI CEI EN 45545-2, CEI EN 61373 |
| **Operating temperatures** | -25° ÷ +65°C |
| **Environmental operating values** | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| **Protection degree** | IP65 (IEC-EN60529) |
| **Protection against impact** | IK04 (IEC-EN62262) |
| **Mechanical durability** | 1.000.000 Operations |
| **Shock resistance** | 30g duration=18ms (EN-IEC 60068-2-27) |
| **Shock resistance** | 50g duration=11ms (EN-IEC 60068-2-27) |
| **Vibration resistance** | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| **Contact blocks configuration** | Max no. 6 blocks (3+3) |
| **External bezel material** | Anodized aluminum |
| **Knob or lever material** | PA Polyamide |
| **Locking ring material** | Zamak zinc alloy |
| **Fixing diameter** | 30.5mm - Thickness 1÷6mm |
| **Tightening torque** | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| **Protection against electric shock** | Class I (IEC-EN61140) |
| **Warranty period** | 18 months |

## Technical drawings

**CAM A**











020E10
020G

**CAM A**






020E01
020E10
020G

