

## Scheda Dati

030SFMAN

Nuppivalitsin, musta, uppoasennus, 2 asentoa, Cam A



## Caratteristiche


|                  |                                                     |
|------------------|-----------------------------------------------------|
| Range            | Vääntökytkimet Ø 30                                 |
| Componente       | 2-asentoiset vääntökytkimet                         |
| Code             | 030SFMAN                                            |
| Kuvaus           | Nuppivalitsin, musta, uppoasennus, 2 asentoa, Cam A |
| Väriä            | Nero                                                |
| Peso             | 45,7                                                |
| Tariffa doganale | 85365080                                            |
| GT               | 8052878036744                                       |

## Dati tecnici

|                                   |                                                  |
|-----------------------------------|--------------------------------------------------|
| Approvals                         | CE, UL, CSA                                      |
| Compliance with standards         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards         | UNI CEI EN 45545-2, CEI EN 61373                 |
| Operating temperatures            | -25° ÷ +65°C                                     |
| Environmental operating values    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)     |
| Protection degree                 | IP65 (IEC-EN60529)                               |
| Protection against impact         | IK04 (IEC-EN62262)                               |
| Mechanical durability             | 1.000.000 Operations                             |
| Shock resistance                  | 30g duration=18ms (EN-IEC 60068-2-27)            |
| Shock resistance                  | 50g duration=11ms (EN-IEC 60068-2-27)            |
| Vibration resistance              | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| Contact blocks configuration      | Max no. 6 blocks (3+3)                           |
| External bezel material           | Anodized aluminum                                |
| Knob or lever material            | PA Polyamide                                     |
| Locking ring material             | Zamak zinc alloy                                 |
| Fixing diameter                   | 30.5mm - Thickness 1÷6mm                         |
| Tightening torque                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| Protection against electric shock | Class I (IEC-EN61140)                            |
| Warranty period                   | 18 months                                        |

Disegni tecnici

CAM A



CAM A

