

Scheda Dati

030SFMLAG

Bouton tournant lumineux à manette, jaune, montage affleurant, 2 positions, Cam A





Caratteristiche

| | |
|-------------------------------------|---|
| Portée | Boutons tournants à manette lumineux Ø 30 |
| Componente | 2 positions |
| Code | 030SFMLAG |
| Désignation des marchandises | Bouton tournant lumineux à manette, jaune, montage affleurant, 2 positions, Cam A |
| Couleur | Giallo |
| Peso | 43,5 |
| Tariffa doganale | 85365080 |
| GTIN | 8052878036973 |

Dati tecnici

| | |
|---|---|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373 |
| Operating temperatures | -25° ÷ +65°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP65 (IEC-EN60529) |
| Protection against impact | IK04 (IEC-EN62262) |
| Mechanical durability | 1.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 4 blocks (2+2) |
| Knob or lever material | PC Polycarbonate |
| External bezel material | Anodized aluminum |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Illuminated selector switch (all versions) | It is mandatory to use LED bulbs type 010BA9SLxxx |
| Protection against electric shock | Class I (IEC-EN61140) |
| Warranty period | 18 months |

Disegni tecnici





CAM A



020E10
020PD9

CAM A



020E01
020E10
020PD9

