Hoja de datos

030SFPLOGC

Selector luminoso con mando, amarillo, hilo panel, 3 posiciones, Cam O, retorno al centro





Características


Rango	Selectores luminosos de mando Ø 30
Componente	Selectores de mando con 3 posiciones
Código	030SFPLOGC
Descripción	Selector luminoso con mando, amarillo, hilo panel, 3 posiciones, Cam O, retorno al centro
Color	Giallo
Peso	36,0
Arancel aduanero	85365080
GTIN	8052878037550


Datos técnicos

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-25° ÷ +65°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK04 (IEC-EN62262)
Mechanical durability	1.000.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 4 blocks (2+2)
Knob or lever material	PC Polycarbonate
External bezel material	Anodized aluminum
Locking ring material	Zamak zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Illuminated selector switch (all versions)	It is mandatory to use LED bulbs type 010BA9SLxxx
Protection against electric shock	Class I (IEC-EN61140)


Warranty period	18 months


Dibujos técnicos





CAM 0









020E10
020E10
020PD9

