

## Scheda Dati

030SLNO2F1C

Selector de palanca, negro, 3 posiciones, Cam O, muelle con retorno al centro, 2 N.O.+2 N.C.



## Caratteristiche

<b>Rango</b>	Selectores de palanca Ø 30
<b>Componente</b>	Selectores con palanca con 3 posiciones
<b>Código</b>	030SLNO2F1C
<b>Descripción</b>	Selector de palanca, negro, 3 posiciones, Cam O, muelle con retorno al centro, 2 N.O.+2 N.C.
<b>Color</b>	Nero
<b>Peso</b>	132,0
<b>Tariffa doganale</b>	85365080
<b>GTIN</b>	8052878037888

## Dati tecnici

<b>Approvals</b>	CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Operating temperatures</b>	-25° ÷ +65°C
<b>Protection degree</b>	IP65 (IEC-EN60529)
<b>Mechanical durability</b>	1.000.000 Operations
<b>Housing material</b>	PA Polyamide
<b>Knob or lever material</b>	PC Polycarbonate
<b>External bezel material</b>	Chromed zinc alloy
<b>Housing material</b>	PA Polyamide + chrome
<b>Fixing diameter</b>	30.5mm - Thickness 1÷6mm
<b>Tightening torque</b>	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Contact block</b>	Included
<b>Contact block characteristics</b>	See technical features of 030FAP - 030FCP - 030F1P
<b>Warranty period</b>	18 months

# Disegni tecnici

## CAM 0

