

Datasheet

030SLNQ2F1

Lever selector switch, black,4-position,Cam Q, 2 N.O.+2 N.C.



Features


| | |
|-----------------------|--|
| Range | Lever selector switches Ø 30 |
| components | 4-position |
| Code | 030SLNQ2F1 |
| Description | Lever selector switch, black,4-position,Cam Q, 2 N.O.+2 N.C. |
| Colour | Nero |
| Weight - gr | 139.0 |
| Customs Tariff | 85365080 |
| GTIN | 8052878038021 |

Datasheet

| | |
|--|--|
| Approvals | CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only) |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +65°C |
| Protection degree | IP65 (IEC-EN60529) |
| Mechanical durability | 1.000.000 Operations |
| Housing material | PA Polyamide |
| Knob or lever material | PC Polycarbonate |
| External bezel material | Chromed zinc alloy |
| Housing material | PA Polyamide + chrome |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Contact block | Included |
| Contact block characteristics | See technical features of 030FAP - 030FCP - 030F1P |
| Warranty period | 18 months |

Technical drawings

CAM Q



(R)



(L)

