


Hoja de datos

030SMLARFAFC24

Selector luminoso de mando, rojo, 2 posiciones, Cam A, led BA9S, N.O.+N.C.



Características

| | |
|-------------------------|--|
| Rango | Selectores luminosos de mando Ø 30 |
| Componente | Selector de mando con 2 posiciones |
| Código | 030SMLARFAFC24 |
| Descripción | Selector luminoso de mando, rojo, 2 posiciones, Cam A, led BA9S, N.O.+N.C. |
| Color | Rosso |
| Peso | 101,0 |
| Arancel aduanero | 85365080 |
| GTIN | 8052878038212 |

Datos técnicos

| | |
|--------------------------------------|--|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +65°C |
| Protection degree | IP65 (IEC-EN60529) |
| Mechanical durability | 1.000.000 Operations |
| Housing material | PA Polyamide |
| Knob or lever material | PC Polycarbonate |
| External bezel material | Chromed zinc alloy |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Bulb type | Ba9S LED 24V AC-DC (included) |
| Contact block | Included |
| Contact block characteristics | See technical features of 030FAP - 030FCP - 030F1P |

Dibujos técnicos

CAM A

