

## Fiche technique

030SMLBBFAFC24

Bouton tournant lumineux à manette, blanc, 2 positions, Cam B, led BA9S, N.O.+N.C.



## Caractéristiques

|                                     |  |
|-------------------------------------|--|
| <b>Portée</b>                       | Boutons tournants à manette lumineux Ø 30  |
| <b>Composant</b>                    | 2 positions  |
| <b>Code</b>                         | 030SMLBBFAFC24   |
| <b>Désignation des marchandises</b> | Bouton tournant lumineux à manette, blanc, 2 positions, Cam B, led BA9S, N.O.+N.C. |
| <b>Couleur</b>                      | Bianco   |
| <b>Poids</b>                        | 101,0  |
| <b>Tarif douanier</b>               | 85365080   |
| <b>GTIN</b>                         | 8052878038236  |

## Données techniques

|                                      |  |
|--------------------------------------|--|
| <b>Approvals</b>                     | CE, UL, CSA  |
| <b>Compliance with standards</b>     | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| <b>Operating temperatures</b>        | -25° ÷ +65°C                                       |
| <b>Protection degree</b>             | IP65 (IEC-EN60529)                                 |
| <b>Mechanical durability</b>         | 1.000.000 Operations                               |
| <b>Housing material</b>              | PA Polyamide                                       |
| <b>Knob or lever material</b>        | PC Polycarbonate                                   |
| <b>External bezel material</b>       | Chromed zinc alloy                                 |
| <b>Fixing diameter</b>               | 30.5mm - Thickness 1÷6mm                           |
| <b>Tightening torque</b>             | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                        |
| <b>Bulb type</b>                     | Ba9S LED 24V AC-DC (included)                      |
| <b>Contact block</b>                 | Included   |
| <b>Contact block characteristics</b> | See technical features of 030FAP - 030FCP - 030F1P |

# Dessins techniques

## CAM B

