

Datablad

030SMLBBFAFC24

Verlichte keuzeknop, wit, 2 posities, Cam B, led BA9S, N.O.+N.C.



Kenmerken

Bereik	Verlichte keuzeknoppen Ø 30
Component	2-positie keuzeknoppen
Rubriek	030SMLBBFAFC24
Omschrijving	Verlichte keuzeknop, wit, 2 posities, Cam B, led BA9S, N.O.+N.C.
Kleur	Bianco
Gewicht	101,0
Douanetarief	85365080
GTIN	8052878038236

Technische gegevens

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	1.000.000 Operations
Housing material	PA Polyamide
Knob or lever material	PC Polycarbonate
External bezel material	Chromed zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Bulb type	Ba9S LED 24V AC-DC (included)
Contact block	Included
Contact block characteristics	See technical features of 030FAP - 030FCP - 030F1P

Technische tekeningen

CAM B

