

## Scheda Dati

030SMLBBLFAFC24

Valoväntökytkin, sininen, 2-asentoinen, Cam B, led BA9S, N.O.+N.C.



## Caratteristiche

<b>Range</b>	Valoväntökytkimet Ø 30
<b>Componente</b>	2-asentoinen vääntökytkin
<b>Code</b>	030SMLBBLFAFC24
<b>Kuvaus</b>	Valoväntökytkin, sininen, 2-asentoinen, Cam B, led BA9S, N.O.+N.C.
<b>Väriä</b>	Blu
<b>Peso</b>	94,0
<b>Tariffa doganale</b>	85365080
<b>GT</b>	8052878038243

## Dati tecnici

<b>Approvals</b>	CE, UL, CSA
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Operating temperatures</b>	-25° ÷ +65°C
<b>Protection degree</b>	IP65 (IEC-EN60529)
<b>Mechanical durability</b>	1.000.000 Operations
<b>Housing material</b>	PA Polyamide
<b>Knob or lever material</b>	PC Polycarbonate
<b>External bezel material</b>	Chromed zinc alloy
<b>Fixing diameter</b>	30.5mm - Thickness 1÷6mm
<b>Tightening torque</b>	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
<b>Bulb type</b>	Ba9S LED 24V AC-DC (included)
<b>Contact block</b>	Included
<b>Contact block characteristics</b>	See technical features of 030FAP - 030FCP - 030F1P

# Disegni tecnici

## CAM B

