

Datasheet

030SMLBRFAFC24

Illuminated knob selector switch, red, 2-position, Cam B led BA9S, N.O.+N.C.



Features

Range	Illuminated knob selector switches Ø 30
components	2-position
Code	030SMLBRFAFC24
Description	Illuminated knob selector switch, red, 2-position, Cam B led BA9S, N.O.+N.C.
Colour	Rosso
Weight - gr	101.0
Customs Tariff	85365080
GTIN	8052878038267

Datasheet

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	1.000.000 Operations
Housing material	PA Polyamide
Knob or lever material	PC Polycarbonate
External bezel material	Chromed zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Bulb type	Ba9S LED 24V AC-DC (included)
Contact block	Included
Contact block characteristics	See technical features of 030FAP - 030FCP - 030F1P

Technical drawings

CAM B

