

## Datenblatt

030SMLBVFAFC24

Beleuchteter Drehknopf-Wahlschalter, grün, 2 Positionen, CAM B, Led BA9S, N.O.+N.C.



## Merkmale

|                        |   |
|------------------------|---|
| <b>Baureihe</b>        | Beleuchtete Drehknopf-Wahlschalter Ø 30   |
| <b>Komponenten</b>     | Drehknopf-Wahlschalter, 2 Positionen  |
| <b>Artikel-Nr.</b>     | 030SMLBVFAFC24  |
| <b>Beschreibung</b>    | Beleuchteter Drehknopf-Wahlschalter, grün, 2 Positionen, CAM B, Led BA9S, N.O.+N.C. |
| <b>Farbe</b>           | Verde   |
| <b>Gewicht - gr</b>    | 94,0  |
| <b>Zolltarifnummer</b> | 85365080  |
| <b>GTIN</b>            | 8052878038274   |

## Dati tecnici

|                                      |  |
|--------------------------------------|--|
| <b>Approvals</b>                     | CE, UL, CSA  |
| <b>Compliance with standards</b>     | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| <b>Operating temperatures</b>        | -25° ÷ +65°C                                       |
| <b>Protection degree</b>             | IP65 (IEC-EN60529)                                 |
| <b>Mechanical durability</b>         | 1.000.000 Operations                               |
| <b>Housing material</b>              | PA Polyamide                                       |
| <b>Knob or lever material</b>        | PC Polycarbonate                                   |
| <b>External bezel material</b>       | Chromed zinc alloy                                 |
| <b>Fixing diameter</b>               | 30.5mm - Thickness 1÷6mm                           |
| <b>Tightening torque</b>             | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                        |
| <b>Bulb type</b>                     | Ba9S LED 24V AC-DC (included)                      |
| <b>Contact block</b>                 | Included   |
| <b>Contact block characteristics</b> | See technical features of 030FAP - 030FCP - 030F1P |

# Disegni tecnici

## CAM B

