

Datenblatt

030SMLOB2FAC24

Beleuchteter Drehknopf-Wahlschalter, weiß, 3 Positionen, Cam O, Led BA9S, Federrücklauf zur mitte, 2 N.O.



Merkmale

Baureihe	Beleuchtete Drehknopf-Wahlschalter Ø 30
Komponenten	Drehknopf-Wahlschalter, 3 Positionen
Artikel-Nr.	030SMLOB2FAC24
Beschreibung	Beleuchteter Drehknopf-Wahlschalter, weiß, 3 Positionen, Cam O, Led BA9S, Federrücklauf zur mitte, 2 N.O.
Farbe	Bianco
Gewicht - gr	101,0
Zolltarifnummer	85365080
GTIN	8052878038298

Technische Daten

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	1.000.000 Operations
Housing material	PA Polyamide
Knob or lever material	PC Polycarbonate
External bezel material	Chromed zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Bulb type	Ba9S LED 24V AC-DC (included)
Contact block	Included
Contact block characteristics	See technical features of 030FAP - 030FCP - 030F1P

Technische Zeichnungen



CAM 0

