

Datenblatt

030SMLOBL2FA24

Beleuchteter Drehknopf-Wahlschalter, blau, 3 Positionen, CAM O, Led BA9S, 2 N.O.





Merkmale

| | |
|------------------------|--|
| Baureihe | Beleuchtete Drehknopf-Wahlschalter Ø 30 |
| Komponenten | Drehknopf-Wahlschalter, 3 Positionen |
| Artikel-Nr. | 030SMLOBL2FA24 |
| Beschreibung | Beleuchteter Drehknopf-Wahlschalter, blau, 3 Positionen, CAM O, Led BA9S, 2 N.O. |
| Farbe | Blu |
| Gewicht - gr | 101,0 |
| Zolltarifnummer | 85365080 |
| GTIN | 8052878038304 |

Technische Daten

| | |
|--------------------------------------|--|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +65°C |
| Protection degree | IP65 (IEC-EN60529) |
| Mechanical durability | 1.000.000 Operations |
| Housing material | PA Polyamide |
| Knob or lever material | PC Polycarbonate |
| External bezel material | Chromed zinc alloy |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Bulb type | Ba9S LED 24V AC-DC (included) |
| Contact block | Included |
| Contact block characteristics | See technical features of 030FAP - 030FCP - 030F1P |

Technische Zeichnungen



CAM 0

