

Scheda Dati

030SMLOG2FA24

Verlichte keuzeknop, geel, 3 posities, Cam O, led BA9S, 2 N.O.



Caratteristiche

Bereik	Verlichte keuzeknoppen Ø 30
Componente	3-positie keuzeknoppen
Rubriek	030SMLOG2FA24
Omschrijving	Verlichte keuzeknop, geel, 3 posities, Cam O, led BA9S, 2 N.O.
Kleur	Giallo
Peso	94,0
Tariffa doganale	85365080
GTIN	8052878038328

Dati tecnici

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	1.000.000 Operations
Housing material	PA Polyamide
Knob or lever material	PC Polycarbonate
External bezel material	Chromed zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Bulb type	Ba9S LED 24V AC-DC (included)
Contact block	Included
Contact block characteristics	See technical features of 030FAP - 030FCP - 030F1P

Disegni tecnici



CAM 0

