

## Fiche technique

030SMNT2F1

Bouton tournant à manette, noir, 3 positions, Cam T, 2 N.O.+2 N.C.



## Caractéristiques


<b>Portée</b>	Boutons tournants à manette non-lumineux Ø 30
<b>Composant</b>	3 positions
<b>Code</b>	030SMNT2F1
<b>Désignation des marchandises</b>	Bouton tournant à manette, noir, 3 positions, Cam T, 2 N.O.+2 N.C.
<b>Couleur</b>	Nero
<b>Poids</b>	139,0
<b>Tarif douanier</b>	85365080
<b>GTIN</b>	8052878038762

## Données techniques

<b>Approvals</b>	CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Operating temperatures</b>	-25° ÷ +65°C
<b>Protection degree</b>	IP65 (IEC-EN60529)
<b>Mechanical durability</b>	1.000.000 Operations
<b>Housing material</b>	PA Polyamide
<b>Knob or lever material</b>	PC Polycarbonate
<b>External bezel material</b>	Chromed zinc alloy
<b>Housing material</b>	PA Polyamide + chrome
<b>Fixing diameter</b>	30.5mm - Thickness 1÷6mm
<b>Tightening torque</b>	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Contact block</b>	Included
<b>Contact block characteristics</b>	See technical features of 030FAP - 030FCP - 030F1P
<b>Warranty period</b>	18 months

# Dessins techniques

CAM T



33 — 34

11 — 12

43 — 44

21 — 22

