

Hoja de datos

040C0715-6

Caja botonera aluminio M4 70x155x62, placa sin orificios, sin entrada cable



Características

Rango	Cajas botoneras aluminio M4 70x155 mm
Componente	Placa aluminio sin orificios
Código	040C0715-6
Descripción	Caja botonera aluminio M4 70x155x62, placa sin orificios, sin entrada cable
Color	Grigio RAL7035
Peso	328,0
Arancel aduanero	85381000
GTIN	8052878039646

Datos técnicos

Approvals	CE, UL, CSA, EAC
UL/CSA Approval	Item will be labelled only upon specific request
Compliance with standards	IEC-EN62208, UL508, CSA C22.2 No.14-13
Operating temperatures	-40° ÷ +100°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK09 (IEC-EN62262)
Manufacturing process	Diecasting
Enclosure material	Aluminum Al Si11 Cu2 (EN AC46100)
Gasket material	Cork rubber
Screw material	Stainless steel AISI 304
Screw type	M4 - cross head Phillips 2
Tightening torque	2,5Nm (22.1 Lb-in)
Painting	Polyester powder coating (except unpainted models)
Protection against electric shock	Class I (IEC-EN61140)
Fitted for outdoor application	yes
Warranty period	18 months

Dibujos técnicos

