

## Datasheet

040C0715-8P3L

Aluminium push-button enclosure M4 70x155x80, 3 holes Ø 22, without cable entry



## Features

<b>Range</b>	Aluminium push-button enclosures M4 70x155 mm
<b>components</b>	3-hole lid Ø 22
<b>Code</b>	040C0715-8P3L
<b>Description</b>	Aluminium push-button enclosure M4 70x155x80, 3 holes Ø 22, without cable entry
<b>Colour</b>	Grigio RAL7035
<b>Weight - gr</b>	414.0
<b>Customs Tariff</b>	85381000
<b>GTIN</b>	8052878039790

## Datasheet

<b>Approvals</b>	CE, UL, CSA, EAC
<b>UL/CSA Approval</b>	Item will be labelled only upon specific request
<b>Compliance with standards</b>	IEC-EN62208, UL508, CSA C22.2 No.14-13
<b>Operating temperatures</b>	-40° ÷ +100°C
<b>Protection degree</b>	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
<b>Protection against impact</b>	IK09 (IEC-EN62262)
<b>Manufacturing process</b>	Diecasting
<b>Enclosure material</b>	Aluminum Al Si11 Cu2 (EN AC46100)
<b>Gasket material</b>	Cork rubber
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	M4 - cross head Phillips 2
<b>Tightening torque</b>	2,5Nm (22.1 Lb-in)
<b>Painting</b>	Polyester powder coating (except unpainted models)
<b>Protection against electric shock</b>	Class I (IEC-EN61140)
<b>Fitted for outdoor application</b>	yes
<b>Warranty period</b>	18 months

## Technical drawings

