

## Scheda Dati

040C0808-8EP2

Painikepaneelikotelo alumiini M10 85x85x85, 2 aukkoa Ø 22, kaapelin sisäänmenolla



## Caratteristiche

|                  |                                                                                   |
|------------------|-----------------------------------------------------------------------------------|
| Range            | Painikepaneelikotelo alumiini M10 85x85 mm                                        |
| Componente       | Kansi 2 aukolla Ø 22                                                              |
| Code             | 040C0808-8EP2                                                                     |
| Kuvaus           | Painikepaneelikotelo alumiini M10 85x85x85, 2 aukkoa Ø 22, kaapelin sisäänmenolla |
| Väriä            | Grigio RAL7016 / Grigio RAL7035                                                   |
| Peso             | 440,0                                                                             |
| Tariffa doganale | 85381000                                                                          |
| GT               | 8052878040093                                                                     |

## Dati tecnici

|                                   |                                                    |
|-----------------------------------|----------------------------------------------------|
| Approvals                         | CE, UL, CSA                                        |
| UL/CSA Approval                   | Item will be labelled only upon specific request   |
| Compliance with standards         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| Operating temperatures            | -40° ÷ +100°C                                      |
| Protection degree                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)  |
| Protection against impact         | IK09 (IEC-EN62262)                                 |
| Manufacturing process             | Diecasting                                         |
| Enclosure material                | Aluminum Al Si11 Cu2 (EN AC46100)                  |
| Gasket material                   | Nitrile rubber                                     |
| Screw material                    | Zamak zinc alloy                                   |
| Screw type                        | M10 - slotted head type 6mm flat blade             |
| Tightening torque                 | 3Nm (26.6 Lb-in)                                   |
| Painting                          | Polyester powder coating (except unpainted models) |
| Protection against electric shock | Class I (IEC-EN61140)                              |
| Fitted for outdoor application    | yes                                                |
| Warranty period                   | 18 months                                          |

## Disegni tecnici

