# Datasheet

040C0814-6P4
Aluminium push-button enclosure M10 85x140x65, 4 holes Ø 22, without cable entry



## Features

| | |
|---|---|
| **Range** | Aluminium push-button enclosures M10 85x140 mm |
| **components** | 4-hole lid Ø 22 |
| **Code** | 040C0814-6P4 |
| **Description** | Aluminium push-button enclosure M10 85x140x65, 4 holes Ø 22, without cable entry |
| **Colour** | Grigio RAL7016 / Grigio RAL7035 |
| **Weight - gr** | 506.0 |
| **Customs Tariff** | 85381000 |
| **GTIN** | 8052878040390 |

## Datasheet

| | |
|---|---|
| **Approvals** | CE, UL, CSA |
| **UL/CSA Approval** | Item will be labelled only upon specific request |
| **Compliance with standards** | IEC-EN62208, UL508, CSA C22.2 No.14-13 |
| **Operating temperatures** | -40° ÷ +100°C |
| **Protection degree** | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| **Protection against impact** | IK09 (IEC-EN62262) |
| **Manufacturing process** | Diecasting |
| **Enclosure material** | Aluminum Al Si11 Cu2 (EN AC46100) |
| **Gasket material** | Nitrile rubber |
| **Screw material** | Zamak zinc alloy |
| **Screw type** | M10 - slotted head type 6mm flat blade |
| **Tightening torque** | 3Nm (26.6 Lb-in) |
| **Painting** | Polyester powder coating (except unpainted models) |
| **Protection against electric shock** | Class I (IEC-EN61140) |
| **Fitted for outdoor application** | yes |
| **Warranty period** | 18 months |

## Technical drawings

