

Hoja de datos

040C0826-6EP8L

Caja botonera aluminio M10 85x260x65, 8 orificios Ø 22, con entrada cable



Características

Rango	Cajas botoneras aluminio M10 85x260 mm
Componente	Tapa con 8 orificios Ø 22
Código	040C0826-6EP8L
Descripción	Caja botonera aluminio M10 85x260x65, 8 orificios Ø 22, con entrada cable
Color	Grigio RAL7016 / Grigio RAL7035
Peso	746,0
Arancel aduanero	85381000
GTIN	8052878041434

Datos técnicos

Approvals	CE, UL, CSA
UL/CSA Approval	Item will be labelled only upon specific request
Compliance with standards	IEC-EN62208, UL508, CSA C22.2 No.14-13
Operating temperatures	-40° ÷ +100°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK09 (IEC-EN62262)
Manufacturing process	Diecasting
Enclosure material	Aluminum Al Si11 Cu2 (EN AC46100)
Gasket material	Nitrile rubber
Screw material	Zamak zinc alloy
Screw type	M10 - slotted head type 6mm flat blade
Tightening torque	3Nm (26.6 Lb-in)
Painting	Polyester powder coating (except unpainted models)
Protection against electric shock	Class I (IEC-EN61140)
Fitted for outdoor application	yes
Warranty period	18 months

Dibujos técnicos

