

## Scheda Dati

040C0920-1P4

Caja botonera aluminio M4 92x205x100, 4 orificios Ø 22, sin entrada cable



## Caratteristiche

|                         |   |
|-------------------------|---|
| <b>Rango</b>            | Cajas botoneras aluminio M4 92x205 mm                                     |
| <b>Componente</b>       | Tapa con 4 orificios Ø 22   |
| <b>Código</b>           | 040C0920-1P4  |
| <b>Descripción</b>      | Caja botonera aluminio M4 92x205x100, 4 orificios Ø 22, sin entrada cable |
| <b>Color</b>            | Grigio RAL7035  |
| <b>Peso</b>             | 750,0   |
| <b>Tariffa doganale</b> | 85381000  |
| <b>GTIN</b>             | 8052878043636   |

## Dati tecnici

|  |  |
|--|--|
| <b>Approvals</b>                         | CE, UL, CSA, EAC                                   |
| <b>UL/CSA Approval</b>                   | Item will be labelled only upon specific request   |
| <b>Compliance with standards</b>         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| <b>Operating temperatures</b>            | -40° ÷ +100°C                                      |
| <b>Protection degree</b>                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)  |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                                 |
| <b>Manufacturing process</b>             | Diecasting   |
| <b>Enclosure material</b>                | Aluminum Al Si11 Cu2 (EN AC46100)                  |
| <b>Gasket material</b>                   | Cork rubber  |
| <b>Screw material</b>                    | Stainless steel AISI 304                           |
| <b>Screw type</b>                        | M4 - cross head Phillips 2                         |
| <b>Tightening torque</b>                 | 2,5Nm (22.1 Lb-in)                                 |
| <b>Painting</b>                          | Polyester powder coating (except unpainted models) |
| <b>Protection against electric shock</b> | Class I (IEC-EN61140)                              |
| <b>Fitted for outdoor application</b>    | yes  |
| <b>Warranty period</b>                   | 18 months  |

## Disegni tecnici

