

## Scheda Dati

040C0926-7EP8

Scatola pulsantiera alluminio M4 92x265x70, 8 fori Ø 22, con entrata cavo



## Caratteristiche

|                         |                                             |
|-------------------------|---------------------------------------------|
| <b>Gamma</b>            | Scatole pulsantiera alluminio M4 92x265 mm  |
| <b>Componente</b>       | Coperchio con 8 fori Ø 22                   |
| <b>Codice</b>           | 040C0926-7EP8                               |
| <b>Descrizione</b>      | Scatola pulsantiera alluminio M4 92x265x70, |
| <b>Colore</b>           | Grigio RAL7035                              |
| <b>Peso</b>             | 750,0                                       |
| <b>Tariffa doganale</b> | 85381000                                    |
| <b>GTIN</b>             | 8052878044589                               |

## Dati tecnici

|                                          |                                                    |
|------------------------------------------|----------------------------------------------------|
| <b>Approvals</b>                         | CE, UL, CSA, EAC                                   |
| <b>UL/CSA Approval</b>                   | Item will be labelled only upon specific request   |
| <b>Compliance with standards</b>         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| <b>Operating temperatures</b>            | -40° ÷ +100°C                                      |
| <b>Protection degree</b>                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)  |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                                 |
| <b>Manufacturing process</b>             | Diecasting                                         |
| <b>Enclosure material</b>                | Aluminum Al Si11 Cu2 (EN AC46100)                  |
| <b>Gasket material</b>                   | Cork rubber                                        |
| <b>Screw material</b>                    | Stainless steel AISI 304                           |
| <b>Screw type</b>                        | M4 - cross head Phillips 2                         |
| <b>Tightening torque</b>                 | 2,5Nm (22.1 Lb-in)                                 |
| <b>Painting</b>                          | Polyester powder coating (except unpainted models) |
| <b>Protection against electric shock</b> | Class I (IEC-EN61140)                              |
| <b>Fitted for outdoor application</b>    | yes                                                |
| <b>Warranty period</b>                   | 18 months                                          |

## Disegni tecnici

