

Datenblatt

040C1515-7E

Bedienpult-Gehäuse Aluminium M4 152x152x70, ungebohrt, mit Kabeleingang



Merkmale

| | |
|------------------------|---|
| Baureihe | Bedienpult-Gehäuse Aluminium M4 152x152 mm |
| Komponenten | Ungebohrter Deckel |
| Artikel-Nr. | 040C1515-7E |
| Beschreibung | Bedienpult-Gehäuse Aluminium M4 152x152x70, ungebohrt, mit Kabeleingang |
| Farbe | Grigio RAL7035 |
| Gewicht - gr | 727,0 |
| Zolltarifnummer | 85381000 |
| GTIN | 8052878045227 |

Dati tecnici

| | |
|--|--|
| Approvals | CE, UL, CSA, EAC |
| UL/CSA Approval | Item will be labelled only upon specific request |
| Compliance with standards | IEC-EN62208, UL508, CSA C22.2 No.14-13 |
| Operating temperatures | -40° ÷ +100°C |
| Protection degree | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact | IK09 (IEC-EN62262) |
| Manufacturing process | Diecasting |
| Enclosure material | Aluminum Al Si11 Cu2 (EN AC46100) |
| Gasket material | Cork rubber |
| Screw material | Stainless steel AISI 304 |
| Screw type | M4 - cross head Phillips 2 |
| Tightening torque | 2,5Nm (22.1 Lb-in) |
| Painting | Polyester powder coating (except unpainted models) |
| Protection against electric shock | Class I (IEC-EN61140) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Disegni tecnici

