

Hoja de datos

040C1515-7N

Caja botonera aluminio M4 152x152x70, en bruto, sin orificios, sin entrada cable



Características

Rango	Cajas botoneras aluminio M4 152x152 mm
Componente	Tapa sin orificios
Código	040C1515-7N
Descripción	Caja botonera aluminio M4 152x152x70, en bruto, sin orificios, sin entrada cable
Color	Non Verniciato
Peso	594,0
Arancel aduanero	85381000
GTIN	8052878045296

Datos técnicos

Approvals	CE, UL, CSA, EAC
UL/CSA Approval	Item will be labelled only upon specific request
Compliance with standards	IEC-EN62208, UL508, CSA C22.2 No.14-13
Operating temperatures	-40° ÷ +100°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK09 (IEC-EN62262)
Manufacturing process	Diecasting
Enclosure material	Aluminum Al Si11 Cu2 (EN AC46100)
Gasket material	Cork rubber
Screw material	Stainless steel AISI 304
Screw type	M4 - cross head Phillips 2
Tightening torque	2,5Nm (22.1 Lb-in)
Painting	Polyester powder coating (except unpainted models)
Protection against electric shock	Class I (IEC-EN61140)
Fitted for outdoor application	yes
Warranty period	18 months

Dibujos técnicos

