

## Scheda Dati

040C1720-1EP12

Caixa botoeira alumínio M4 170x205x100, 12 furos Ø 22, com entrada cabo



## Caratteristiche

|                  |                                                                         |
|------------------|-------------------------------------------------------------------------|
| Gama             | Caixas botoeiras alumínio M4 170x205 mm                                 |
| Componente       | Tampa com 12 furos Ø 22                                                 |
| Código           | 040C1720-1EP12                                                          |
| Descrição        | Caixa botoeira alumínio M4 170x205x100, 12 furos Ø 22, com entrada cabo |
| Cor              | Grigio RAL7035                                                          |
| Peso             | 1694,0                                                                  |
| Tariffa doganale | 85381000                                                                |
| GTIN             | 8052878045463                                                           |

## Dati tecnici

|                                   |                                                    |
|-----------------------------------|----------------------------------------------------|
| Approvals                         | CE, UL, CSA, EAC                                   |
| UL/CSA Approval                   | Item will be labelled only upon specific request   |
| Compliance with standards         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| Operating temperatures            | -40° ÷ +100°C                                      |
| Protection degree                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)  |
| Protection against impact         | IK09 (IEC-EN62262)                                 |
| Manufacturing process             | Shell gravity diecasting                           |
| Enclosure material                | Aluminum Al Si12 Cu (EN AC47000)                   |
| Gasket material                   | Cork rubber                                        |
| Screw material                    | Stainless steel AISI 304                           |
| Tightening torque                 | 2,5Nm (22.1 Lb-in)                                 |
| Painting                          | Polyester powder coating (except unpainted models) |
| Protection against electric shock | Class I (IEC-EN61140)                              |
| Fitted for outdoor application    | yes                                                |
| Warranty period                   | 18 months                                          |

# Disegni tecnici

