


## Scheda Dati

040C1720-8

Painikepaneelikotelo alumiini M4 170x205x80, levy ilman aukkoja, ilman kaapelin sisäänmenoa



## Caratteristiche

<b>Range</b>	Painikepaneelikotelo alumiini M4 170x205 mm
<b>Componente</b>	Alumiinilevy ilman aukkoja
<b>Code</b>	040C1720-8
<b>Kuvaus</b>	Painikepaneelikotelo alumiini M4 170x205x80, levy ilman aukkoja, ilman kaapelin sisäänmenoa
<b>Väriä</b>	Grigio RAL7035
<b>Peso</b>	1416,0
<b>Tariffa doganale</b>	85381000
<b>GT</b>	8052878045739

## Dati tecnici

<b>Approvals</b>	CE, UL, CSA, EAC
<b>UL/CSA Approval</b>	Item will be labelled only upon specific request
<b>Compliance with standards</b>	IEC-EN62208, UL508, CSA C22.2 No.14-13
<b>Operating temperatures</b>	-40° ÷ +100°C
<b>Protection degree</b>	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
<b>Protection against impact</b>	IK09 (IEC-EN62262)
<b>Manufacturing process</b>	Shell gravity diecasting
<b>Enclosure material</b>	Aluminum Al Si12 Cu (EN AC47000)
<b>Gasket material</b>	Cork rubber
<b>Screw material</b>	Stainless steel AISI 304
<b>Tightening torque</b>	2,5Nm (22.1 Lb-in)
<b>Painting</b>	Polyester powder coating (except unpainted models)
<b>Protection against electric shock</b>	Class I (IEC-EN61140)
<b>Fitted for outdoor application</b>	yes
<b>Warranty period</b>	18 months

## Disegni tecnici

---

